

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
28 October 2004 (28.10.2004)


PCT

(10) International Publication Number  
**WO 2004/092812 A1**

- (51) International Patent Classification<sup>7</sup>: G02F 1/133 (74) Agent: YOU ME PATENT & LAW FIRM; Teheran Bldg., 825-33, Yoksam-dong, Kangnam-Ku, Seoul 135-080 (KR).
- (21) International Application Number: PCT/KR2004/000882 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 16 April 2004 (16.04.2004) (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 10-2003-0024375 17 April 2003 (17.04.2003) KR
- (71) Applicant (for all designated States except US): SAM-SUNG ELECTRONICS CO., LTD. [KR/KR]; 416, Mae-tan-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 442-742 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LEE, Baek-Woon [KR/KR]; Hyundai Home Town 208-1701, 862, Dongcheon-ri, Suji-eup, Yongin-si, Gyeonggi-do 449-843 (KR).
- Published:  
— with international search report

[Continued on next page]

(54) Title: LIQUID CRYSTAL DISPLAY



(57) Abstract: A liquid crystal display includes a plurality of subpixels respectively having switching elements and arranged in a matrix, a plurality of gate lines connected to the subpixels via the switching elements and transmitting a gate signal for turning on or off the switching elements, and a plurality of data lines connected to the subpixels via the switching elements and transmitting a data voltage. The respective subpixels are located in areas defined by two adjacent gate lines and two adjacent data lines, which are uniquely connected to a pair of gate line and data line, and at least one of the subpixels is connected to the different gate lines or the data line positioned at opposite side with respect to the other subpixel of the same row. In this case, a pair of subpixels adjacent above and below are connected to the gate line therebetween or the gate lines positioned at opposite side each other. In this way, any inversions for each color can be performed without changing conventional driving ICs.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*